


LIGHT RING LR06 AND LR08 PENDANT



Light Ring LR06 and LR08 Pendant Configurations



LR06



LR08

(continued on next page)

11828 NE 112th Street
Kirkland, WA 98033
(tel) 425.823.4560 / 800.755.0471
(fax) 425.823.8654
sales@charlesloomis.com
www.charlesloomis.com

June 2009

CHARLES LOOMIS, INC.
Loomis

LIGHT RING LR06 AND LR08 PENDANT

Light Ring LR06 and LR08 Pendant Specifications



Dimensions:

Small Profile:

LR06

Diameter: 23 1/2"
Overall Drop: 80" (*Adjustable*)

LR08

Diameter: 28 1/2"
Overall Drop: 80" (*Adjustable*)

Large Profile:

LR06

Diameter: 39"
Overall Drop: 80" (*Adjustable*)

LR08

Diameter: 47 1/2"
Overall Drop: 80" (*Adjustable*)

Materials/Finishes:

Metal:

Aluminum: Mill Silver CL660
Stainless Steel: Swivels, Cables,
& Sleeving

Lamping (Included):

Small Profile:

MRC16 20W or 50W
PAR20 50W Halogen

Large Profile:

PAR30 75W
PAR38 90W, 150W, 250W Halogen

Supply Voltage:

120V

Listing:

UL or ETL Dry Location

Mounting:

Small Profile:

Direct to Junction Box

Large Profile:

Additional Mounting
Points Required

Approx. Weight:

Small Profile = 22 – 30 lbs.

Large Profile = 38 lbs.

Optional Accessories:

Small Profile:

Hexcell Louvers, Lenses

Large Profile:

Cube Cell Louvers, Lenses

General Notes:

FOB - Kirkland, WA

Lamps are adjustable in Pan & Tilt
& Frames may be Locked into Place.

Designed by Charles Loomis

Contact:

sales@charlesloomis.com
425.823.4560
800.755.0471

**Please contact your local
Representative for pricing and
availability.**